

Distributor cabinet

according DIN 43870 bdew-guideline 2008
 inspected according VDE 0660 Teil 500 / IEC 439-1
 inspected by TÜV according DIN EN 60439-5


protection class of cabinet : IP 44
 class of protection II (with electrical insulation)
 made of : fibreglass-reinforced polyester
 (SMC process), IEC-695-2-1, halogen-free
 colour : grey , similar to RAL 7035
 lock: simple locking
 (with Euro profile half cylinder lock inside)

contains the following items:

- 4-pole busbar system 30x5mm
- 1xNH2-vertical disconnection fuse
- 3xNH00-vertical disconnection fuse
- cover protection against accidental contact
- cable clamp rail in the cabinet

optional:

- filling material for socket SFM1
- dual swing handle
- RAL-painting on the outside



Typ of cabinet

GSAB 35S1710

H : 1710

W : 350

D : 280

			Datum	28.12.10	project: distributor cabinet	Ang.-Nr.:		
			Bearb.	J.Drechsler		oder-no: 35S17KLSSL2+3LSL00	Auf.-Nr.:	
			Gepr.			Urspr.	Ers.f.	Ers.d.
Zust.	Anderung	Datum	Name	Norm				



GSAB
 Elektrotechnik GmbH

Lindenstraße 23 Tel: 49/03636/7614-76 Bl. 1 v.
 99718 Greußen Fax: 49/03636/7614-30 1 Bl.