

Distributor cabinet

according DIN 43870 bdew-guideline 2008
 inspected according VDE 0660 Teil 500 / IEC 439-1
 inspected by TÜV according DIN EN 60439-5


protection class of cabinet : IP 44
 class of protection II (with electrical insulation)
 made of : fibreglass-reinforced polyester
 (SMC process), IEC-695-2-1, halogen-free
 colour : grey , similar to RAL 7035
 lock: single swing handle
 (with Euro profile half cylinder lock inside)

contains the following items:

- 4-pole busbar system 30x5mm
- cover protection against accidental contact
- cable clamp rail in the cabinet


optional:

- filling material for socket SFM1
- dual swing handle
- RAL-painting on the outside



typ of cabinet:
 GSAB 88S1700
 H : 1064+665
 W : 883
 D : 272

socket must be ordered seperately !!!

			Datum	08.01.2013	distributor order-no: 88S1700K 400A	Ang.-Nr.: Auf.-Nr.:	 GSAB Elektrotechnik GmbH	=		
			Bearb.	M.Biermann					+	
Zust.	Anderung	Datum	Name	Norm	Urspr.	Ers.f.	Ers.d.	Lindenstraße 23 99718 Greußen	Tel: 49/03636/7614-76 Fax: 49/03636/7614-30	Bl. 1 v. 1 Bl.