

Distributor cabinet

according DIN 43870 bdew-guideline 2008
 inspected according VDE 0660 Teil 500 / IEC 439-1
 inspected by TÜV according DIN EN 60439-5


protection class of cabinet : IP 44
 class of protection II (with electrical insulation)
 made of : fibreglass-reinforced polyester
 (SMC process), IEC-695-2-1, halogen-free
 colour : grey , similar to RAL 7035
 lock: single swing handle
 (with Euro profile half cylinder lock inside)

contains the following items:

- 4-pole busbar system 30x5mm
- 3xNH2-vertical disconnection fuse
- 5x100mm reserve place
- cover protection against accidental contact
- cable clamp rail in the cabinet

optional:

- filling material for socket SFM1
- dual swing handle
- RAL-painting on the outside



typ of cabinet:
 GSAB 88S1700
 H: 1064+665
 B: 883
 T: 272

socket must be ordered seperately !!!

		Datum	23.12.2010	project: distributor cabinet	Ang.-Nr.:	
		Bearb.	A. Fiedler	order-no: 88S1700K400A-3LSL2	Auf.-Nr.:	
		Gespr.				
Zust. Änderung	Datum	Name	Norm	Urspr.	Ers.f.	Ers.d.



GSAB
 Elektrotechnik GmbH

Lindenstraße 23 Tel: 49(0)3636/7614-76
 99718 Greußen Fax: 49(0)3636/7614-50

BL 1 v.
 1 Bl.