

Distributor cabinet

according DIN 43870 bdeu-guideline 2008
 inspected according VDE 0660 Teil 500 / IEC 439-1
 inspected by TÜV according DIN EN 60439-5


protection class of cabinet : IP 44
 class of protection II (with electrical insulation)
 made of : fibreglass-reinforced polyester
 (SMC process), IEC-695-2-1, halogen-free
 colour : grey , similar to RAL 7035
 lock: simple lock
 (with Euro profile half cylinder lock inside)

contains the following items:

- 4-pole busbar system 30x10mm
- 4xNH2-vertical disconnection fuse
- 8xNH00-vertical disconnection fuse
- cover protection against accidental contact
- cable clamp rail in the cabinet


optional:

- filling material for socket SFM1
- dual swing handle
- RAL-painting on the outside



socket must be ordered seperately !!!

typ of cabinet:
 GSAB 88S1700
 H : 1064+665
 W: 883
 D : 272

Name: 23.12.2010		project: distributor cabinet		Ang-Nr:	
Zust: 2. Freigabe		order-no: 88S17K-4LSL2-8LSL00		Auf-Nr:	
Vom: Andreas		Datum: 11.04.11		Firma:	
				 GSAB Elektrotechnik GmbH	
				48769 Gießen Tel: 49(0)561/9164-0 60719 Gießen Fax: 49(0)561/9164-20	