Distributor cabinet

according DIN 43870 bdew-guideline 2008
inspected according VDE 0660 Teil 500 / IEC 439-1
inspected by TÜV according DIN EN 60439-5

protection class of cabinet : IP 44
class of protection II (with electrical insulation)
made of : fibreglass-reinforced polyester
(SMC process), IEC-695-2-1, halogen-free
colour : grey , similar to RAL 7035
lock: simple lock
(with Euro profile half cylinder lock inside)

<u>contains the following items:</u>

- 4-pole busbar system 30x10mm
- 5xNH2-vertical disconnection fuse
- 6xNH00-vertical disconnection fuse
- cover protection against accidental contact
- cable clamp rail in the cabinet

<u>optional:</u>

- filling material for socket SFM1
- dual swing handle
- RAL-painting on the outside



<u>typ of cabinet:</u>
GSAB 88S1700
H : 1064+665
W: 883
D : 272

<u>socket must be ordered seperately !!!</u>

Zust.	Änderung	Datum	Name						
				Datum	23.12.2010	project: distributor cabinet	Ang.-Nr.:	GSAB Elektrotechnik GmbH	
				Bearb.	A.Fiedler	order-no: 88S17K-5LSL2-6LSL00	Auf.-Nr.:		
				Gepr.					Lindenstraße 23, 99718 Greußen; Tel: 49/03636/7614-76; Fax: 49/03636/7614-30
				Norm		Urspr. / Ers.f.	Ers.d.		Bl. 1 v. 1 Bl.